

DECOPRIME

WALL PRIMER- Water Thinnable

ASIAN PAINTS DECOPRIME WALL PRIMER (WT) IS SUITABLE FOR USE AS A PRIMER FOR PAINTING OF WATER- BASED WALL FINISHES SUCH AS DISTEMPERS AND PLASTIC EMULSIONS.



WATER BASED

asianpaints

No Added Mercury, Arsenic & Chromium

Lead contents does not exceed 90 parts per million.

PRODUCT BENEFITS

Asian Paints Decoprime Wall Primer (WT) can be thinned to application viscosity by adding appropriate amount of water. Its special features are easy brushing , excellent covering, alkali resistance , quick drying and good sealing properties. It is specially fortified with fungicides.


PRODUCT FEATURES

AVAILABLE PACKS



Shelf life: 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

COLOURS AVAILABLE



White

COVERAGE


On smooth wall putty surface by brushing



2 COATS


90-100 Sq. Ft/ lit/ 2 coats

DRYING TIME TO TOUCH



20 MINS

RECOMMENDED USAGE



Can be used for priming plastered walls, asbestos, brick work, concrete, etc

RECOMMENDED APPLICATION

APPLICATION	CODE	THINNER	DILUTION %	APPLICATION VISCOSITY	RECOATING PERIOD
• SANDING	SAND THE SURFACE WITH EMERY PAPER 180 AND WIPE CLEAN				
• DECOPRIME WALL PRIMER (WT) BRUSH / SPRAY	0360	WATER	1:1	BRUSH 20 - 22	3 - 4 HRS
• ACRYLIC WALL PUTTY PUTTY KNIFE	1354	WATER	BASED ON REQUIREMENT	SUPPLY CONSISTENCY	4 - 6 HRS
• SANDING	SAND THE SURFACE WITH EMERY PAPER 180 AND WIPE CLEAN				
• DECOPRIME WALL PRIMER (WT) BRUSH / SPRAY	0360	WATER	1:1	BRUSH 20-22	3 - 4 HRS
• SANDING	SAND THE SURFACE WITH EMERY PAPER 320 AND WIPE CLEAN				

- As measured through a Ford cup.
- Recoat period is quoted for 25°C and 50% Relative Humidity, these may vary under different conditions.
Mineral Turpentine Oil

ADDITIONAL INFORMATION

POST PAINTING CARE

For the best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth, if any, at regular interval of six months.

TECHNICAL DETAILS

- a) Drying time : Surface dry time 30 min
- b) Flash point IS101/1987 Part 1, Sec 6 : NA
- c) Stability of thinned paint : to be used within 24 hours

PRECAUTIONS

- > Kindly refer to the MSDS for Asian Paints Decoprime Wall Primer which gives detailed information on safety measures while handling the paint.
- > Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- > Do not over-thin or over-extend the brush.
- > Tint using Asian Paints machine colourants only.
- > Stir well and strain before use.
- > Tinted paints need thorough shaking immediately after tinter addition as well as before use.

SAFETY AND ENVIRONMENT FEATURES

- > Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- > Keep out of reach of children and away from eatables.
- > May be harmful if swallowed. In case of ingestion, seek immediate medical attention.
- > Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.
- > In case of skin contact, immediately wash skin with soap and plenty of clean water. Get medical attention, if irritation develops or persists.
- > Do not breathe vapor or spray. It is recommended to wear mask during sanding and surface preparation to avoid dust inhalation.
- > Do not pour leftover paint down the drain or in water courses.
- > In the event of spills, contain spillage using sand or earth and dispose through authorized agency for waste management.
- > No added Lead, Mercury, Arsenic, Chromium & Ammonia compounds.
- > Left-Over paint disposal:
 - Left-over paint/drums should not be disposed in soil/drains. Consumer should consult a local recycling agency for disposal of paint/drums.
 - The pails/drums should not be used for storing food items.



For enquiries, feedback and complaints, please call toll-free number 16600124680/9802033515 or write to us at weassure@asianpaints.com.np